










SPECIFICATIONS:

1. CURRENT RATING: 3.0A MAX
2. DIELECTRIC WITHSTAND VOLTAGE: 100VAC
3. TEMPERATURE RANGE: -30 °C ~ 85 °C
4. CONTACT RESISTANCE: 40 MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
6. INSERTION FORCE : 5N~20N
7. UNMATING FORCE: 8N~20N
8. DURABILITY:10,000 CYCLES



5	WATERPROOF RING	SILICA GEL		1
4	Medium iron sheet	SUS304 1/2H		1
3	OUTER SHELL	ZINC ALLOY	NI PLATING	1
2	CONTACT	C7025;	Au3u"PLATING T=0.15mm	16
1	HOUSING	PA10T	COLOR BLACK	1
NO.	DESCRIPTION	MATERIAL	REMARKS	QTY

Guangdong Tengjun Electronic Technology Co., Ltd

DRAWING NO:

JN16-BPS018-A

REV A0 SIZE: A4




PART NAME WATERPROFF TYPE C 16PIN


PART NO. JN16-BPS018-A

TOLERANCE UNLESS OTHERWISE SPECIFIED:
X ±0.2
X.X ±0.15
X.XX ±0.10
X.XXX ±0.050

DRAWING:	Li	DATE:	2019.11.12	SCALE	1:1
CHECK:	Chen	DATE:	2019.11.12	SHEET	1/2
APPROVAL:	Yuan	DATE:	2019.11.12		



THICKNESS T=0.8mm
DEFAULT TOLERANCE+/-0.05



A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND			VBUS	CC1	DP1	DN1	SBU1	VBUS			GND
GND			VBUS	SBU2	DN2	DP2	CC2	VBUS			GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1

PIN NO.	A1&B12	A4&B9	B8	A5	B7	A6	A7	B6	A8	B5	A9&B4	A12&B
SIGNAL NAME	GND	VBUS	SBU2	CC1	DN2	DP1	DN1	DP2	SBU1	CC2	VBUS	GND
PCB PAD NO.	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12